



12" Rotary Pump
Model W12R - E60
Size: 12" Rotary Pump

Holland® Pump Company
Corporate Office: 2610 Sidney Lanier Drive
Brunswick, Georgia 31525
Phone 912-466-0304
1-888-997-PUMP
www.hollandpump.com

PUMP SPECIFICATIONS


Pump Model: LobePro GL531d
Solids: Handles up to 2.5" compressible soft solids
Rated Capacities: 0 - 2656 GPM @ 500 RPM
Displacement: 531 US gallons per 100 revolutions
Working Pressure: to 87 psi
Flange Connections: 10" Flat Face ANSI, 150 lbs. Flange connections included
Rated Speed: 0 - 500 RPM. Consult factory for recommended operating speeds
Rotors in: Helix four wing rotors, NBR standard, other materials available on request
Wet-Ends: Standard in Gray Cast Iron
Shaft Material: Alloy Steel, AISI 4140
Gear Material: AGMA Class 8, SAE 1045
Mechanical Seals: 4 Duronit vs. Duronit cartridge seals
Vibration: Pumps and motors operate at any point within their operating range without undue noise and vibration
Top and Bottom Housing Segments: ASTM A48 Class 30 gray cast iron coated with ceramic epoxy for wear resistance; options include Ryton® and Tungsten Carbide. Segments adjustable based on wear.
Approx. Skid Base weighth (lbs.): 3600
Sound Level: Holland Pump pump units are tested for Sound Level using the Contractors Pump Bureau Sound Level Measurement Standard for Pump Units using a calibrated Sound Level Meter. This procedure produces an average Sound Level based on eight measurements under strict conditions of pump placement. They are tested at full RPM pumping water. The sound Level result for the W12R-E60 is 60 dBA @ 23 feet.

GEAR SPECIFICATIONS

Type: Gear motor
Gear Ratio: 3.72

ELECTRIC SPECIFICATIONS

Type: Baldor
Motor power: 60 hp
Input/Output speed: 1770/473 rpm
Output torque: 8,000 lb-in
Service factor: 2.2
Ratio: 3.72
Mode of operation: Cont.-S1
Insulation class: F
Enclosure: TE-IP55
Voltage: 460V, 60 Hz
Rated current: 85
Output shaft: Diameter = 2.500 inch.; Length = 5.00 inch
Weight appr.: 1,000 pounds without options
Lubricant: Synthetic Oil ISO VG220, ca. 6.87 quarts
Paint coatings: Stainless steel paint
Gear design: Foot mounted (B3)
Gear box options: Quadrilip seals
Motor options: CUS: UL/CSA-standard, HE: Energy efficient motor



GL531d Rotary Pump

Optional Features: Electric control systems, Pump monitoring and shutdown

BASE

Fabricated Steel base, primed and painted

Warranty: One year 100% standard warranty. Our warranty covers parts and labor, including wear for a period of 12 months.




**12" Rotary Pump
Model W12R - E60
Size: 12" Rotary Pump**

Holland® Pump Company
Corporate Office: 2610 Sidney Lanier Drive
Brunswick, Georgia 31525
Phone 912-466-0304
1-888-997-PUMP
www.hollandpump.com

Max operating pressure: 87 psi
(not allowed for continuous operation)

LobePro GL531d Performance Curve



LobePro GL531d Horsepower Requirement

