



**PRIME<sup>3</sup> Vacuum Assisted Suction Pump**  
**Model PT4TMS - P404D22 Super Silent**  
**Size 4" Trash, Materials, Sludge Pump**

Holland® Pump Company  
 Corporate Office: 2610 Sidney Lanier Drive  
 Brunswick, Georgia 31525  
 Phone 912-466-0304  
 1-888-997-PUMP  
 www.hollandpump.com

**PUMP SPECIFICATIONS**

**Type/Model:** Solids and slurry handling/Cornell 4NNDH EM Redi Prime

**Volute:** Fine gray cast iron

**Flanges:** 4" suction, 4" discharge

**Impeller:** 2 Vane open Delta® impeller 10.09" diameter fine gray iron

**Solids:** Handles 3" compressible, spherical solids

**PRIME<sup>3</sup> Priming System:** Automatic dry priming and repriming system that features a 50 cfm water tolerant, diaphragm vacuum pump driven by the main drive shaft. Our major competitors use a 15 cfm compressor pump with a small compressor venturi that can easily clog. The air/water separator is a simple, reliable stainless steel float that opens and closes a rubber plunger as water rises and falls. A non return valve isolates the pump during priming and protects against back flow

**Discharge Valve:** Val-matic or equal

**Seal:** Cornell patented Cycloseal® design with Run-Dry oil lubrication system. Single mechanical seal with Viton® Elastomers, stainless steel hardware and tungsten versus silicon-carbide seal faces for abrasion

**Shaft Sleeve:** Heat treated 416 stainless steel

**Bearings:** Heavy duty, grease lubricated, deep groove ball bearings, with a minimum of 50,000 hours bearing life

**SOUND ENCLOSURE SPECIFICATIONS**

**Sound Level:** Holland Pump Supersilent pump units are tested for Sound Level using the Contractors Pump Bureau Sound Level Measurement Standard for Pump Units using a calibrated Sound Level Meter. This procedure produces an average Sound Level based on eight measurements under strict conditions of pump placement. They are tested at full RPM pumping water. The sound level result is 68 dBA or less @ 23 feet.

**Enclosure:** Steel construction, removable for ease of maintenance.

Stainless steel accessories including bolt on, lift off hinges.

**Base:** Environmentally safe spill containment type base

**Lifting Access:** External lifting bail, integral forklift pockets

**ENGINE SPECIFICATIONS**

**Model:** Perkins 404D-22

**Type:** 4 Cylinder, 4 Stroke, Naturally Aspirated, Liquid Cooled Diesel Engine, Tier 3

**Displacement:** 2.2L (134 cu. in.)

**Governor:** Mechanical

**Lubrication:** Forced Circulation

**Air Cleaner:** Dry Type with Replaceable Element

**Lube Oil Capacity:** 2.8 U.S. gal (10.6 L)

**Coolant Capacity:** 1.84 U.S. gal (6.98 L)

**Fuel Tank:** Integral 114 U.S. Gallon Capacity (#2 Diesel Fuel)

**Full Load Operating Time:** 60 Hours Minimum

**Starter:** 12 Volt, 2 kW

**Standard Features:** Skid, SAE Flywheel Housing, SAE Flywheel, Murphy Safety Shutdown System Covering: Engine Oil Pressure, High Water Temperature

**Optional Features:** Site or DOT Highway Trailer, Automatic Remote Start/Stop, HANS (Holland Automatic Notification System), NEMA 4 Instrument Package Covering: Air Filter, Fuel Filter, Engine Temperature, Fuel Level, Engine Oil Pressure, Hour Meter, Amp Meter

**Coupling:** Stromag coupling

PT4TMS-P404D22-SS			Shutoff Head: 111 feet		
Flow (GPM)	Speed (RPM)	TDH (ft)	Pump Efficiency (%)	Power (hp)	Max Suction Head (ft)*
746	1770	72.9	61	22.6	16.7
627**	1770	80.1	61	20.7	18.5
622	1770	80.4	61	20.6	18.6
498	1770	87.8	60	18.3	20.4
373	1770	96	56	16.1	21.9
249	1770	95.2	47	12.7	22

\*Max Suction Head is suction lift plus friction losses without risk of suction cavitation  
 \*\*Best Efficiency Point

**Perkins Published Performance:** Power: 51 BHP Continuous @ 3000 RPM



**PRIME<sup>3</sup>** Vacuum Assisted Suction Pump  
Model PT4TMS - P404D22 Super Silent  
Size 4" Trash, Materials, Sludge Pump

Holland® Pump Company  
Corporate Office: 2610 Sidney Lanier Drive  
Brunswick, Georgia 31525  
Phone 912-466-0304  
1-888-997-PUMP  
www.hollandpump.com

Approximate Dimensions  
Powered by Perkins 404D-22 Diesel Engine

	Skid Base	DOT Trailer
Net Weight (lbs)	3110	3510
Shipping Weight (lbs)	3300	N/A
Export Crate Size (cu. ft)	130	N/A



Performance Curve Model: PT4TMS - Super Silent - P404D22  
Size: 4" Trash, Materials, Sludge Pump

